

Carpenter's Skew Notch, Lap-Joint and Tenon Cutting Machine ZK 115 Ec up to maschine no. 1013785

ref.no.: 925001_1013785

EAN:

▶ Attention: Just spare parts are still available



Technical data

Cutting depth at 0°	0 - 2 12/16 Inch
Tilt range	0 - 60 °
Nominal No. of strokes – no load	4050 1/min
Nominal power input	4.0 hp
Weight (with standard cutter head)	46.5 lbs
Universal motor	230 V / 50 Hz

Delivery specification

1 Cutter head, cpl., Ø 150 x 115 mm (5 7/8 x 4 1/2 in.); Ref. No. 203657

1 Parallel guide fence; Ref. No. 203683

1 Allen key 10 mm; Ref. No. 093164

1 Screw driver Torx T 15; Ref. No. 093274

Applications

- ▶ Birdsmouth cuts and lap joints
- ▶ Compatible materials include solid wood and glue-laminated timber

Advantages

- ▶ All-round protective cover – for optimum user protection.
- ▶ Special machine – for all notching and facing tasks.
- ▶ Fast, precise adjustment – no test cutting necessary – considerable time-saving.

Description

The ZK 115 Ec – a persuasive and powerful tool offering ease of use, a tool brake and electronics with: - Smooth starting - Constant speed under load - Overload protection - No-load speed reduction to protect machine - Reduced noise emissions

The entirely newly developed 150 x 115 mm (5 7/8 x 4 1/2 in.) cutter head of the ZK 115 Ec, with 13 reversible carbide tips (9 for final, 4 for rough cutting), facilitates very high cutting rates, optimum chip removal and an extended service life.

Simply score the notch and vertical cut, set the cut indicator, notch depth and angle – and mortising can begin. It couldn't be quicker or easier!

The guide rails available as optional accessories can be used with all other MAFELL carpentry machines.

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de