

Pull-Push Saw ERIKA 60 E - TRC up to machine no. 1202715

ref.no.: 971525_1202715

EAN:

- ▶ boxed
- ▶ Attention: Just spare parts are still available



Technical data

Cutting height	1/16 - 2 3/8 Inch
Cutting height at 45°	1/16 - 1 5/8 Inch
Tilt range	-2 - 47 °
Cutting length	8 9/16 Inch
Table top dimensions	16 1/4 x 21 7/16 Inch
Nominal power input	1.7 hp
Weight	46.3 lbs
Universal motor	230 V / 50 Hz
Working height with stand	12 3/16 Inch
Working height without stand	33 1/4 Inch

Delivery specification

- 1 Mains cable 4 m (13.1 ft); Ref. No. 097765
- 1 TCT saw blade 190 x 1.2/2.0 x 30 mm (7 1/2 in.), AT, 36 teeth, for universal use in wood; Ref. No. 092550
- 1 Universal guide fence with fence extension; Ref. No. 200941
- 1 Extraction hose with 2 connectors; Ref. No. 093639
- 1 Push stick; Ref. No. 034901
- 1 Mains cable 4 m (13.1 ft)

examples for usage



Applications

- ▶ Cross and rip cuts
- ▶ Circular saw bench functionality
- ▶ Bevel cuts up to 47°
- ▶ Compatible materials include solid wood, board materials, parquet and laminate flooring, aluminum profiles and plastics

Advantages

- ▶ New type of suction channel revolutionises extraction - for less dust when working.
- ▶ Maximum cutting height of 61 mm (2 3/8 in.) – with a material thickness of 12 mm (1/2 in.), a cutting length of 215 mm (8 7/16 in.) is achieved.
- ▶ For hidden cuts – the riving knife can be lowered with no effort.
- ▶ With voltage loss switch for protection against uncontrolled reconnection after a power interruption.

Description

With optimum air flow in the suction channel, chips can be more easily removed by your dust extractor.

At 21 kg (46.3 lbs), the ultra-lightweight is convenient for use on any floor. Whether in the cellar or in the attic – the ERIKA 60 E can be carried quickly and effortlessly from one workplace to another.

Operation of the ERIKA 60 E is simple in its design concept. Clearly designed operating elements are all arranged logically on the front of the machine. Over 30 years of experience have gone into every detail. Stability where it's needed – on the table! Especially when cutting, the craftsman exerts pressure on the workpiece and thus also on the benchtop.

Stability where it's needed - on the table! Especially when cutting, the craftsman exerts pressure on the workpiece and thus also on the benchtop.

Attention ERIKA-users: All accessories of the previous models ERIKA 55 and ERIKA 60 can continue to be used on the new ERIKA 60 E.

Accessories / Tools



Extension table

No longer available



Extension table ERIKA 60

requires 2 support/mounting rails



Supporting rail

650 mm (25 9/16 in.) long



Supporting rail

840 mm (33 1/16 in.) long



TCT saw blade

190 x 1.4/2.0 x 30 mm (7 1/2 in.), AT, 36 teeth,
for universal use



TCT saw blade

180 x 1.4/2.0 x 30 mm (7 1/16 in.), AT, 30 teeth,
for universal use



TCT saw blade

180 x 1.2/2.0 x 30 mm (7 1/16 in.), AT, 56, teeth



Dust bag

No longer available



Fold-away support



Fence guide extension

with telescopic rod and drop stop



Universal guide fence

with fence extension



Sliding table

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de