

Cross-Cutting System KSS 400 - GB 110 V until Masch. No. 954594

ref.no.: 916522_954594

EAN:

▶ Attention: Just spare parts are still available

Technical data

Cutting depth at 0° with guide track	0 - 1 15/16 Inch
Cutting depth 45° with track	0 - 1 1/2 Inch
Cutting depth at 0° without guide track	0 - 2 13/16 Inch
Tilt range	0 - 45 °
Cutting length	15 3/4 Inch
Angle cuts	-60 - +60 °
Nominal No. of strokes – no load	5200 1/min
Nominal power input	1.5 hp
Weight with guide rail	11.5 lbs
Universal motor	110 V

Accessories / Tools



Lever clamp F-SZ 180MM
2 pieces, for fixing guide rail to workpiece



Guide rail F 110
1.1 m (3.6 ft) long



Guide rail F 160
1.6 m (5.2 ft) long



Guide rail F 210
2,1 m (6,9 ft) long



Guide rail F 310
3,1 m (10,2 ft) long



TCT saw blade
160 x 1.2/1.8 x 20 mm (6 5/16 in.), AT, 16 teeth,
for rip cuts in wood



Guide pocket F 160
for guide rails up to 1,6 m



Guide pocket set
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 180MM
+ Guide pocket



Non-slip profile F-HP 6,8 M
6.8 m (22.3 ft.) long



Flexible hose FXS-L
up to 3,2 m (10.6 ft) long



Guide track ML
max. cutting length 770 mm (30 5/16 in.)



Guide rail F 80
0,8 m (2,6 ft) long



Carrying case TK
785x320x285 mm, with insert



Mushroom-shaped handle
as additional machine guide, with fixing screw



TCT saw blade
160 x 1.2/1.8 x 20 mm (6 5/16 in.)/ AT, 32 teeth,
for fine cuts in wood



Connecting piece F-VS
for joining two guide rails



Angle fence F-WA



Guide pocket set
2 x F 160 + F-VS + 2 x F-SZ 180 MM + 1 guide
pocket



End cap F-EK
2 pieces



Splinter guard F-SS 3,4M
3.4 m (11.2 ft.) long



Parallel guide fence
with wing screws

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de