

## Portable Circular Saw K 85 Ec in L-Max - USA 120 V up to maschine no. 1074326

ref.no.: 918233\_1074326

EAN:

▶ Attention: Just spare parts are still available



### Technical data

Cutting depth	0 - 3 7/16 Inch
Cutting depth at 45°	0 - 2 7/16 Inch
Cutting depth at 60°	1/16 - 1 3/4 Inch
Tilt range	0 - 60 °
Weight	14.8 lbs
Universal motor	120 V / 60 Hz
Nominal power input	2.4 hp
Nominal No. of strokes – no load	1/min

### Delivery specification

- 1 TCT saw blade 237 x 1.8/2.5 x 30 mm (9 5/16 in.), AT, 12 teeth, for rip cuts in wood; Ref. No. 092590
- 1 Parallel guide fence; Ref. 205323
- 1 Hose connector for chip extraction; Ref. No. 205290
- 1 Allen key 5 mm; Ref. No. 093034
- 1 Mains cable 4 m - GB 110 V; Ref. No. 087803

## Applications

---

- ▶ Cross-cutting and rip cuts
- ▶ Bevel/compound miter cuts up to 60°
- ▶ Birdsmouth cuts
- ▶ Plunge cuts
- ▶ Chamfers and grooves
- ▶ Compatible materials include solid wood, board materials, insulating materials, doors, worktops and internal finishing and renovation materials

## Advantages

---

- ▶ The K 85 / K 85 Ec offers an enhanced cutting depth of up to 88 mm (3 7/16 in.). Even when used in conjunction with the guide rail, it achieves an exceptional depth of 82 mm (3 3/16 in.).
- ▶ Optimum chip ejection, especially when sawing insulating materials.
- ▶ Sawing to mark. The pointer adjusts automatically to the set tilt angle.
- ▶ The cutting depth is set and locked in a single, quick action.
- ▶ Thanks to the new tilting arrangement of the K 85 / K 85 Ec, reading the scale is easier than ever before.

## Description

---

The MAFELL portable circular saw combines power and precision with ease of use and ergonomic design. These properties transform the machine into a unique system.

Sheer power and high torque take on a whole new meaning with the new high-output CUprex motor. It offers performance-optimized digital electronics and newly developed control technology. Its speed is continuously variable according to the nature of the material and application.

It is no longer necessary to unscrew the riving knife – the FLIPPKEIL offers you optimum user-friendliness and safety when plunge cutting.

## Accessories / Tools



**Lever clamp F-SZ 180MM**  
2 pieces, for fixing guide rail to workpiece



**Parallel guide fence**



**Roller edge guide**  
K 85-UA



**L-MAX**  
with insert



**TCT saw blade**  
237 x 1.8/2.5 x 30 mm (9 5/16 in.), AT, 12 teeth  
for rip cuts in wood



**TCT saw blade**  
237 x 1.8/2.5 x 30 mm (9 5/16 in.), AT, 24 teeth,  
for rip cuts and cross-cutting in wood



**TCT saw blade**  
237 x 1.8/2.5 x 30 mm (9 5/16 in.), AT, 56 teeth  
for cross-cutting in wood



**Guide pocket F 160**  
for guide rails up to 1,6 m



**Guide pocket set**  
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 180MM  
+ Guide pocket



**Non-slip profile F-HP 6,8 M**  
6.8 m (22.3 ft.) long



**Suction clamping system Aeroxfix F-AF 1**  
with 1,3 m rail, adapters for above and  
underneath rail, flexible hose



**Guide rail F 80**  
0,8 m (2,6 ft) long



**Guide rail F 110**  
1.1 m (3.6 ft) long



**Guide rail F 160**  
1.6 m (5.2 ft) long



**Guide rail F 210**  
2,1 m (6,9 ft) long



**Guide rail F 310**  
3,1 m (10,2 ft) long



**Connecting piece F-VS**  
for joining two guide rails



**Angle fence F-WA**



**Guide pocket set**  
2 x F 160 + F-VS + 2 x F-SZ 180 MM + 1 guide  
pocket



**End cap F-EK**  
2 pieces



**Splinter guard F-SS 3,4M**  
3.4 m (11.2 ft.) long



**Flexible hose FXS-L**  
up to 3,2 m (10.6 ft) long

## contact

---

MAFELL AG

Beffendorfer Straße 4  
D-78727 Oberndorf / Neckar  
Germany

Tel.: +49 7423 / 812-114  
Fax: +49 7423 812-102  
Email: [export@mafell.de](mailto:export@mafell.de)